




WRC02...SOR圆导轨混合滑台 Assembled hybrid carriages



产品特性 Product features

- 滚动与滑动混合滑台
 - 顺畅滑动，较小驱动力
 - 导向滑动膜标准材料EPB13
 - 配合WR02导轨侧向安装
 - 自润滑、免维护
 - 抗灰尘、无噪音
- Rolling and sliding hybrid carriages
 - Smooth moving and lower driving force
 - Sliding liners material: EPB13
 - For side installation of WR02 guide rails
 - Maintenance-free, dry-running
 - Resistant dust and no noise

标准规格 Standard specifications



产品编码 Part No.:

WRC02-10-40-100-SOR02

- 单侧滚轮数量
Roller quantities on one side
- 侧向安装 Side installation
- 长度 Length
- 宽度 Width
- 直径 Diameter

产品编码 Part No.	A [mm]	A ₁ [mm]	L [mm]	C [mm]	H [mm]	K ₃ [mm]	A ₂ [mm]	C ₁ [mm]	静态载荷 Static load			动态载荷 Dynamic load	重量 Weight [kg]
									Coy- [N]	Mox [Nm]	Coz [N]	Coz [N]	
WRC02-10-40-100-SOR02	73	60	100	87	30	M6	5	40	2400	170	920	2560	0.35
WRC02-10-40-150-SOR02	73	60	150	137	30	M6	5	80	2400	290	920	2560	0.39
WRC02-10-40-200-SOR02	73	60	200	187	30	M6	5	80	2400	410	920	2560	0.45
WRC02-10-80-100-SOR02	107	94	100	87	30	M6	5	40	2400	170	920	2560	0.48
WRC02-10-80-150-SOR02	107	94	150	137	30	M6	5	80	2400	290	920	2560	0.55
WRC02-10-80-200-SOR02	107	94	200	187	30	M6	5	80	2400	410	920	2560	0.60
WRC02-16-60-150-SOR02	104	86	150	132	42	M8	5	70	4200	480	1440	3880	1.00
WRC02-16-60-200-SOR02	104	86	200	182	42	M8	5	70	4200	690	1440	3880	1.10
WRC02-20-80-150-SOR02	134	116	150	132	53	M8	7	58	6400	670	1760	4400	1.30
WRC02-20-80-200-SOR02	134	116	200	182	53	M8	7	100	6400	990	1760	4400	1.40
WRC02-20-80-250-SOR02	134	116	250	232	53	M8	7	100	6400	1250	1760	4400	1.60