


WRC01圆导轨滑台 Assembled guide carriages



产品特性 Product features

- 标准滑动膜EPB13
 - 带夹紧手轮设计
 - 相机固定 3/8" 螺纹孔
 - 自润滑、免维护
 - 重量轻、抵抗灰尘
- Sliding liners material: EPB13
 - With locking handwheel design
 - 3/8" threaded hole for camera
 - Self-lubricating, maintenance-free
 - Lightweight and resistant to dust

标准规格 Standard specifications



产品编码 Part No.:

WRC01-10-40-100-CHL

- C: 相机孔 Camera hole
- H: 手轮 Handwheel
- L: 锁紧装置 Locking device
- 长度 Length
- 宽度 Width
- 直径 Diameter

产品编码 Part No.	A [mm]	A ₂ [mm]	C [mm]	C ₂ [mm]	H _{+0.2} [mm]	K ₂ [mm]	T [mm]	静态载荷 Static load					重量 Weight [kg]
								Co _y [N]	Co _z [N]	Mo _x [Nm]	Mo _y [Nm]	Mo _z [Nm]	
WRC01-10-40-100-CHL	73	60	100	87	24	M6	22.5	4800	2400	96	170	170	0.35
WRC01-10-40-150-CHL	73	60	150	137	24	M6	22.5	4800	2400	96	290	290	0.39
WRC01-10-40-200-CHL	73	60	200	187	24	M6	22.5	4800	2400	96	410	410	0.45
WRC01-10-80-100-CHL	107	94	100	87	24	M6	22.5	4800	2400	178	170	170	0.48
WRC01-10-80-150-CHL	107	94	150	137	24	M6	22.5	4800	2400	178	290	290	0.55
WRC01-10-80-200-CHL	107	94	200	187	24	M6	22.5	4800	2400	178	410	410	0.60
WRC01-16-60-150-CHL	104	86	150	132	35	M8	33.5	8400	4200	240	480	480	1.0
WRC01-16-60-200-CHL	104	86	200	182	35	M8	33.5	8400	4200	240	690	690	1.1
WRC01-20-80-150-CHL	134	116	150	132	44	M8	33.5	12800	6400	525	670	670	1.3
WRC01-20-80-200-CHL	134	116	200	182	44	M8	33.5	12800	6400	525	990	990	1.4
WRC01-20-80-250-CHL	134	116	250	232	44	M8	33.5	12800	6400	525	1250	1250	1.6